



# LAWNNAIRE® 28

The **F**irst Name in Turf Renovation™

The LAWNNAIRE 28 (LA 28) vertical coring aerator delivers value by saving your business time, money and effort. Simply stated, the LA 28 pulls the optimum number of cores in less time than other walk-behind aerators on the market.

Engineered for performance, dependability and low maintenance, the LA 28 is built with heavy gauge steel throughout and sealed precision bearings. An ergonomic design ensures operator comfort and higher productivity.

## OUTPERFORMS DRUM STYLE AERATORS

- Pulls cores even in difficult soil conditions
- Produces more holes in a single pass
- Self-propelled and easy to maneuver requiring less effort
- Vertical coring means the turf is ready for play more quickly

## SUSTAINABLE TURF CARE

- Effective in reducing soil compaction
- Promotes stronger grass root growth and air exchange
- Improves nutrient and water absorption
- Reduces need for fertilizers and pesticides



*The rear drive differential and front caster wheel makes the LA 28 easy to maneuver.*



## FEATURES:

- Honda GX200 5.5hp engine
- Self-propelled: chain drive rear differential
- Front castor wheel
- Dual chain tine drive system
- 24,000 sq. ft. per hour
- Up to 12 holes per sq. ft.
- 2.5" coring depth
- Remote engine kill switch
- Extra set of 0.75" X 2.5" tines included

**For more information, please visit [www.ryanturf.com](http://www.ryanturf.com),  
or call us at 1.866.469.1242**

# LAWNNAIRE® 28 AERATOR

**Superior performance and productivity means faster payback,  
making the LA 28 an ideal choice for the commercial grounds care industry.**

## POWER

### Honda GX200

Engine .....4-cycle, Honda® GX200™; recoil starter; on/off switch; muffler  
Horsepower (@ 3,600 rpm) .....5.5 hp (4.1 kW)  
Displacement .....11.9 cu. in. (196 cc)  
Oil Capacity .....0.6 qt. (0.63 L)

### Briggs & Stratton

Engine .....4-cycle, Briggs & Stratton® Vanguard™; recoil starter; on/off switch; muffler  
Horsepower (@ 3,600 rpm) .....7.5 hp (5.6 kW)  
Displacement .....13.1 cu. in. (215 cc)  
Oil Capacity .....1 qt. (0.9 L)

## UNIT

Machine Type .....Reciprocating self-propelled walk behind aerator  
Clutch .....Belt Tightener  
Drive  
Wheel .....A-section V-belt, #40 Nickel plated roller chain  
Tines .....B-section V-belt, #50 Nickel plated roller chain  
Aerating Width .....28 in. (711 mm)  
Coring Depth .....Up to 2.5 in. (64 mm)  
Core Diameter .....0.75 in. (19 mm)  
Aeration Pattern .....3.5 in. x 5 in. (89 mm x 127 mm)  
Number of Holes .....up to 12/sq. ft. (129/m<sup>2</sup>)  
Productivity .....Aerates up to 24,000 sq. ft./hr (2230 m<sup>2</sup>/hr)  
Transport .....2.1 mph (3.3 km/h)  
Tines .....Hollow, tapered, austemper-hardened steel; 3/4 in. (19 mm) diameter tines  
Tine Arms .....4 arms; 2 tines per arm  
Tires  
Front .....10.4 x 4.10/3.50, 4-ply  
Rear .....8.7 x 2.80/2.50, 4-ply  
Brakes .....Automatic parking brake  
Handles .....Rubber isolated handlebars  
Tine Engagement Mechanism .....Spring-assist  
Bearings .....Sealed precision bearings  
Lubrication .....5 grease fitting  
Reversing gearbox .....Oil bath  
Differential .....Grease

## DIMENSIONS

Width .....34 in. (864 mm)  
Length .....56.4 in. (1.4 m)  
Height .....48 in. (1.2 m)  
Weight  
Model 544887 (Honda engine) .....404 lbs. (183 kg)  
Model 544874E (B & S engine) .....400 lbs. (181 kg)

## WARRANTY

**All Ryan products come with a  
2 year commercial warranty.**

Specifications, while correct at the time of printing,  
may change without notice.

Ryan® is a registered trademark of Schiller Grounds Care, Inc.  
© 2009 Schiller Grounds Care, Inc.

One Bob Cat Lane • Johnson Creek, WI 53038 • [www.ryanturf.com](http://www.ryanturf.com)

Your Local Dealer Is: