

SPECIFICATIONS

WRIGHT SENTAR®



RUBBER CHUTE DEFLECTOR



Cutting Width	48"	52"	61"
---------------	-----	-----	-----

MOWER

Cutting Height Range	1.0 - 5.25"	1.0 - 5.25"	1.0 - 5.25"
Deck Lift System	Rapid-Hite™	Rapid-Hite™	Rapid-Hite™
Deck Construction	7 Gauge	7 Gauge	7 Gauge
Blades (1/4" thick, high-lift wings)	(3) 16.5"	(3) 18"	(3) 21"
Blade Tip Speed (fpm at 3584 rpm)	19,000	19,000	19,000
Spindles	Cast Iron Housings	Cast Iron Housings	Cast Iron Housings
Blade Clutch/Brake Maintenance-Free; Rated Heavy Duty	Warner™	Warner™	Warner™
Discharge Systems	Side, Rear & Mulch	Side, Rear & Mulch	Side, Rear & Mulch

REINFORCED DISCHARGE



ENGINE

Makes Available	Kawasaki™	Kawasaki™	Kawasaki™
Horsepower	19, 23	23, 25	23, 25
Cylinders	2	2	2
Starting	Electric	Electric	Electric
Hour Meter	Included	Included	Included
23 & 25 hp equip w/ heavy duty air cleaner			

QUAD LEVER™ CONTROLS



TRACTOR

Operator Controls	Quad Lever™	Quad Lever™	Quad Lever™
Hydro Pumps	16 cc	16 cc	16 cc
Fuel Capacity	10.7 Gal.	10.7 Gal.	10.7 Gal.
Drive Tires	23 x 9.5 - 12	23 x 9.5 - 12	23 x 9.5 - 12
Caster Tires	13 x 5.0 - 6	13 x 5.0 - 6	13 x 5.0 - 6
Speed Forward (mph)	11	11	11
Speed Reverse (mph)	5	5	5

TURBO TEN INSTALLED



DIMENSIONS

Overall Length	65"	65"	70"
Overall Width - Deflector Up (Down)	49" (59")	53" (63")	62" (72")
Dry Weight	905 - 950	905 - 950	905 - 950

Warranty 2-year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer.

To find the name of your nearest dealer, please visit www.wrightmfg.com

COMING SOON TO A WRIGHT DEALER NEAR YOU!

For more information, call 1.301.360.9810 or find our dealer locator at www.wrightmfg.com.

THE WRIGHT WAY TO MOW.

